
# DF-130E Cost-Effective Oxygen Analysis

**The DF-130E** with the E-Sensor provides a cost effective solution for a wide range of oxygen analysis needs – no sensor replacement and little or no recalibration.

#### Improved Speed of Response (figure 3)



#### **Superior Performance**

The analyzer is delivered calibrated and ready to use

### Accuracy

The greater of +/- 3% Reading or 0.5% of Range Below 2.5 ppm

#### **Fast Response**

- Instantaneous response to oxygen change
- Fast response, typically less than 10 seconds to read 90% of a step change

For more information about the DF-130E, the 100E Series or the E-Sensor, visit www.delta-f.com.

## **DF-130E Specifications**

#### Range

Ranges are available from 0-10 ppm to 0-25%

## Sample Gas Compatibility

Standard Sensor – All inert and passive gases including  $N_2$ ,  $H_2$ , CO, freons, hydrocarbons, etc.

Sensor With STAB-EL<sup>™</sup> Option – Neutralizes trace contaminants including acids Such as CO<sub>2</sub>, H<sub>2</sub>S, No<sub>x</sub>, So<sub>x</sub>, etc. (Consult Delta F for concentration limits)

## Options

Öxygen Alarm Sample Pump STAB-EL<sup>™</sup> Acid Gas System Classified Area Enclosures CE Certification

Accuracy

 $\pm$  2% Full Scale at constant temperature (±5 % below 0-2.5 ppm) Response Time

Responds simultaneously to  $O_2$  change. Equilibrium time depends on specific conditions Typically less than 10 seconds to read 90% of a step change

#### Sample Requirements

Gas phase, non-condensing, 0 to 150°F Flow should be 1.0 to 3.0 SCFH at 0.2 to 1.0 psig pressure **Misc.** 19.7 cm W x 21.6 cm H x 25.4 cm D 7kg (7.75"Wx8.5"Hx10"D 15 lbs.) Operate between 0° and 45° C ambient (32° and 120° F) 115 VAC or 220 VAC at 25 Watts



## **Configuration and Installation**

Delta F provides comprehensive assistance for a broad variety of problems including application sample gases with acids, hydrocarbons, particles and other contaminants. Depending on the model, Delta F analyzers can be configured to provide a wide choice of outputs for data collection and process control systems. Most Delta F analyzers can be configured for remote operation and all can be ordered with classified area enclosures. Contact your Delta F rep for an Applications Data Sheet and pricing information.



Delta F Corporation 4 Constitution Way Woburn, MA 01801-1087 USA

Tel: (781) 935-4600 Fax: (781) 938-0531

e-mail: <u>marketing@delta-f.com</u> <u>www.delta-f.com</u>