



DETAIL A

FOR MORE INFO
SEE REF MANUAL

- 1 WHEN NPT THREAD ADAPTER IS USED SUITABLE TAPER THREAD SEALING SHALL BE USED.
- 2 P/T RATING FOR THIS FLANGE, SEE REF MANUAL.
- 3 LIQUID LEVEL ABOVE ROD END REQUIRES SPECIAL SETTINGS.
- 4 MAX NOZZLE HEIGHT 100 mm FOR ROD 100. MAX NOZZLE HEIGHT 250 mm FOR ROD 250.
- 5 ALL DIMENSIONS IN mm UNLESS OTHERWISE STATED.

POS	ITEM DESCRIPTION	QTY	REMARK	SUPPLIER
04	GASKET	1	SOFT GASKET T=MIN 1.6 (ANSI B16-5/1A, EN1514-1/IBC) SEE NOTE 1	CUSTOMER
03	TEFLON PLATE (OPTIONAL)	1	Ø102 FOR DN50/JIS50 AND ANSI 2" FLANGE Ø136 FOR DN80/JIS80 AND ANSI 3" FLANGE Ø162 FOR DN100/JIS100 AND ANSI 4" FLANGE Ø218 FOR DN150/JIS150 AND ANSI 6" FLANGE Ø270 FOR DN200/JIS 200 AND ANSI 8" FLANGE	RMT
02	SCREW/NUT/WASHER	1	ACC. TO FLANGE STD SEE NOTE 2	CUSTOMER
01	THREADED APPL.	1	DIM. ACC. TO ANSI B 16.5/ EN 1092-1. OTHER ON REQUEST P/T RATING SEE NOTE 2 ANSI/ASME PIPE THREAD 1 1/2"-11, 5 NPT SEE NOTE 1	RMT

ISSUED BY	WEK	PRODUCT CODE	FILE	INSTALLATION DRAWING TITLE
GU-TK-T0	0524	5400	PRO/E	MECHANICAL INSTALLATION DWG
APPROVED BY	WEK	ORIGINAL DWG. NO.	SCALE	
		9240030-977	4:25	5400, ROD ANTENNA
ROSEMOUNT		1 ST ANGLE	DOC TYPE	DWG NO.
			2	9240030-977
			ISSUE	SHEET
			01	1/1