



RACO Manufacturing and Engineering Co., 1400 62nd St., Emeryville, CA 94608 (510) 658-6713 800-722-6999 FAX (510) 658-3153

AMPS ANALOG CELLULARM SYSTEM DC Powered Model

April, 2002

RACO's Cellularm System represents the next generation of fixed cellular equipment designed to provide voice and data communications over the cellular network. The Cellularm System can be used for cellular telephone communications only, or it can be optionally equipped with a RACO autodialer to provide additional alarm monitoring and reporting capabilities.

Designed for temporary or permanent field use, the new system is ruggedly built and is housed in a heavy duty, weather-resistant enclosure. Fully equipped, the Cellularm System consists of a 3 watt analog cellular transceiver, antenna, and one of RACO's family of autodialers packaged in a single, integrated unit.

It is the users responsibility to contact his local cellular dealer or service provider to determine the availability of an AMPS analog network.

TECHNICAL SPECIFICATIONS

• **Cellular Transceiver**

Analog for Amps, 3 watt, telephone handset programmable, 15 month factory warranty.

• **Transceiver Power**

DC Input Voltage Range 10.5 to 15.0 VDC

• **Transceiver Battery Backup**

Two 6 volt 4 AH, sealed lead acid batteries. External battery operation equals 1 hour active use, 8 hours standby. 25 Watts Maximum, 6 watts, Typical Standby

• **Antenna**

Cellularm furnished with a flexible right angle, 2.5 dB gain antenna, connected to a standard TNC connector. If system is to be located in a cellular fringe area or a hilly location, a higher strength antenna may be required (to be furnished by owner).

• **Telephone Connection**

One standard RJ 11C connector provided for standard telephone set or autodialer. User to furnish splitter if both telephone set and autodialer are to be used together.

• **Environment**

Operating Temperature Range: -10 degrees C to +55 degrees C

Storage Temperature Range: -25 degrees C to +65 degrees C

Humidity Range: 5% to 95% (excludes batteries)

• **Enclosure Specifications**

Molded fiberglass with silicone gaskets NEMA 3, 4X, 12; CSA Type 3, 4, and 5; UL Approved

• **Overall Dimensions**

Guard-It System: 17-1/2" H x 15-1/2" W x 6-1/4" D

All Other Systems: 17-1/2" H x 14-7/8" W x 12-1/4" D

Mounting Centers: 16-3/4" vertical x 12" horizontal

• **Total Weight**

Guard-It System 29 lbs, all other Systems 49 lbs. Includes entire packaged system — fiberglass enclosure, cellular telephone with backup battery pack, and autodialer.